



**commands**      **message commands**

# Message Commands List

List of all `message commands` available in the bot.

```
The prefix for the bot is ) or m! or minato
i.e. either of following would work
)help
m!help
minato help
```

Also by mentioning Minato you invoke commands i.e.  
@Minato Namikaze help

And in DM's only m! works i.e. only m!help in DM's

```
Use ")help command" for more info on a command.
Use ")help category" for more info on a category.
Use the dropdown menu below to select a category.
```

Support Server

For more help, consider joining the official server over at <https://discord.gg/vfXHwS3nmQ>

How do I use this bot?

Reading the bot signature is pretty simple.

<argument>

This means the argument is required.

[argument]

This means the argument is optional.

[A|B]

This means that it can be either A or B.

[argument...]

This means you can have multiple arguments.

Now that you know the basics, it should be noted that...

You do not type in the brackets!

## Shinobi Match

An amazing shinobi match with your friends

## - match

Play shinobi match with your friends using the characters from `Naruto Verse`

Parameters Required: `opponent`

Usage: `[prefix]match <opponent.mention>`

Aliases: `shinobi_match, matchwith, shinobimatch, match_with`

## QuickPoll

Create polls

## - polltime

Create polls easily

Aliases: `poll, polls`

## - tally

Get polls results

Parameters Required: `poll_id`

Usage: `[prefix]tally <poll id>`

Aliases: `result, results`

## - quickpoll

Makes a poll quickly.

Parameters Required: `questions_and_choices`

# Anime, Manga and Waifu

Some anime, manga and waifu related commands

## - animesearch

Searches Anime from MAL and displays the first 10 search result.

Parameters Required: anime\_name

Usage: [prefix]animesearch <anime.name>

Aliases: anisearch, animesearchbyname, anime\_search\_by\_name, searchanime, searchani

## - aboutanime

Displays about the anime using the MAL ANIME ID. get it by using animesearch command.

Parameters Required: mal\_id

Usage: [prefix]aboutanime <mal.id>

Aliases: aniabout, animeabout, anime\_about\_by\_mal\_id, knowanime, aboutani, anime

## - mangasearch

Searches Manga from MAL and displays the first 10 search result.

Parameters Required: manga\_name

Usage: [prefix]mangasearch <manga.name>

Aliases: magsearch, mangasearchbyname, manga\_search\_by\_name, searchmanga, searchmag

## - aboutmanga

Displays about the manga using the MAL MANGA ID. get it by using mangasearch command.

Parameters Required: mal\_id

Usage: [prefix]aboutmanga <mal.id>

Aliases: magabout, mangaabout, manga\_about\_by\_mal\_id, knowmanga, aboutmag, manga

## - waifu

Get random waifu and marry them! UwU!

Aliases: w, wfu, wa

## - whosthatpokemon

Play Who's That Pokemon?

Aliases: wtp, whatsthatpokemon

## Vocaloid

Get some kawai pictures of the vocaloids.

### - rin

Rin kawai picture

### - una

Una kawai picture

- gumi

Gumi kawai picture

- ia

Ia kawai picture

- luka

Luka kawai picture

- fukase

Fukase kawai picture

- miku

Hatsune Miku kawai picture

- len

Len kawai picture

- kaito

Kaito kawai picture

- teto

Teto kawai picture

- meiko

Meiko kawai picture

- yukari

Yukari kawai picture

- miki

Miki kawai picture

- lily

Lily kawai picture

- mayu

Mayu kawai picture

- aoki

Aoki kawai picture

- zola

Zola kawai picture

- diva

Random picturs from Project Diva

## Invites

Get invites information about the server

- `invitestats`

Displays the top 10 most used invites in the guild.

## My Support

Having problems with me? Then you can get the help here.

- `vote`

Get all the voting links

- `about`

Tells you information about the bot itself.

```
Aliases: stats
```

- `invite`

Generates my invite link for your server

```
Aliases: invite
```

- `supportserver`

Generates my support server invite

- `privacy`

Get the Privacy Policy



- ping

Get the Latency

- source

Displays my full source code or for a specific command.

Parameters Required: command

## Info

Get's the Information about the server

- avatar

Get the avatar of you or someone else

Parameters Required: user

- joinedat

Check when a user joined the current server

Parameters Required: user

- server

Check info about current server

Aliases: serverinfo

## - server\_icon

Parent: [server](#)

Get the current server icon

```
Aliases: icon
```

## - banner

Parent: [server](#)

Get the current banner image

## - user

Get user information

```
Parameters Required: user
```

```
Aliases: whois, who, userinfo
```

## Snipe

“Snipes” someone’s message that’s been edited or deleted.

## - snipe

“Snipes” someone’s message that’s been edited or deleted.

## Support

Displays the support command for the server, this can only be used if the owner has enabled it

## - support

Open support ticket if enabled by the server admins

## - resolved

Resolves the existing ticket!

Parameters Required: member

Usage: [prefix]resolved <member.mention>

Aliases: resolve, resolves

## - chksupreq

Checks who still requires the support.

Aliases: check\_who\_require\_support, cksupreq, supreq, sup\_req, checksupport, check\_support

## - feedback

Sends your feedback about the server to the server owner. (This can only be done if it is enabled by the server admin)

Parameters Required: feed

## Weather

Get weather data from <https://openweathermap.org>

## - weather

Display weather in a given location

Parameters Required: location

Aliases: we

- CO

Parent: [weather](#)

Display weather in a given location

Parameters Required: lat, lon

Aliases: coords, coordinates

- zip

Parent: [weather](#)

Display weather in a given location

Parameters Required: zipcode

- cityid

Parent: [weather](#)

Display weather in a given location

Parameters Required: cityid

## Encoding

Convert messages into fun encodings

## - charinfo

Shows you information about a number of characters.

Parameters Required: characters

## - hash

Various hashing commands

## - md5

Parent: [hash](#)

MD5 Encrypt Text

Parameters Required: txt

## - sha1

Parent: [hash](#)

SHA1 Encrypt Text

Parameters Required: txt

## - sha256

Parent: [hash](#)

SHA256 Encrypt Text

Parameters Required: txt

## - sha512

Parent: [hash](#)

## SHA512 Encrypt Text

Parameters Required: txt

### - encode

Encode a string.

### - rot

Parent: [encode](#)

Encode a caesar cipher message with specified key

Parameters Required: rot\_key, message

Aliases: caesar

### - braille

Parent: [encode](#)

Encode text into braille unicode characters

Parameters Required: message

### - b16

Parent: [encode](#)

Encode text into base 16

Parameters Required: message

Aliases: base16

## - b64

Parent: [encode](#)

Encode text into base 64

Parameters Required: message

Aliases: base64

## - hex

Parent: [encode](#)

Encode text into hexadecimal

Parameters Required: message

## - b32

Parent: [encode](#)

Encode text into base 32

Parameters Required: message

Aliases: base32

## - chr

Parent: [encode](#)

Encode message into character numbers

Parameters Required: message

Aliases: character

## - dna

Parent: [encode](#)

Encodes a string into DNA 4 byte ACGT format

Parameters Required: message

## - binary

Parent: [encode](#)

Encode text into binary sequences of 8

Parameters Required: message

## - decode

Decode a string.

## - b32

Parent: [decode](#)

Decode base32 text

Parameters Required: message

Aliases: base32

## - chr

Parent: [decode](#)

Decode character numbers to a message

Parameters Required: message



Aliases: character

## - binary

Parent: [decode](#)

Decode binary sequences of 8

Parameters Required: message

## - b16

Parent: [decode](#)

Decode base16 text

Parameters Required: message

Aliases: base16

## - rot

Parent: [decode](#)

Decode a caeser cipher message with specified key

Parameters Required: rot\_key, message

Aliases: caeser

## - b64

Parent: [decode](#)

Decode base 64 text

Parameters Required: message

Aliases: base64

## - braille

Parent: [decode](#)

Decode braille unicode characters to ascii

Parameters Required: message

## - dna

Parent: [decode](#)

Decodes a string of DNA in 4 byte ACGT format.

Parameters Required: message

## - hex

Parent: [decode](#)

Decode a hexadecimal sequence to text

Parameters Required: message

## Games

Play some amazing games

## - tictactoe

Play Tictactoe with yourself or your friend!

Parameters Required: member

Usage: [prefix]tictactoe <other player.mention>

Aliases: tc

## - connectfour

Play Amazing Connect Four Game

Parameters Required: member

Usage: [prefix]connectfour [other player.mention]

Aliases: connect\_four, c4, cf

## - hangman

Play Hangman!

Aliases: hg

## - akinator

Play Akinator

Aliases: aki

## - typeracer

Check your typing speed via a simple typeracer test

Aliases: wpm, typingspeed

- chatbot

Talk with me!

```
Aliases: cb
```

- reaction

Yum Yum or Yuck Yuck?

## Elements

Display information from the periodic table of elements

- element

Display information about an element

```
Parameters Required: element, measurement
```

- elements

Display information about multiple elements

```
Parameters Required: elements
```

- ptable

Display a menu of all elements

## Random

Some random fun and usefull commands.

## - braille

Parameters Required: user

## - insult

Insult a user

Parameters Required: user

Usage: [prefix]insult <member.mention>

Aliases: takeitback

## - owoify

Owoify the message

Parameters Required: text

Usage: [prefix]owoify {text}

## - magic

See magic!

Parameters Required: user

## - qr

Generates easy QR Code

Parameters Required: colour, url

## - remind

A simple reminder

```
Parameters Required: time, reminder
```

```
Usage: [prefix]remind <time> <reminder> (Time needs to be in seconds...)
```

## - sn

Introduce yourself to everyone

```
Parameters Required: name
```

```
Usage: [prefix]sn <name>
```

## - tts

Generate text to speech messages

```
Parameters Required: text
```

```
Usage: [prefix]tts <text>
```

## - show\_color

Enter a color and you will see it!

```
Parameters Required: color
```

```
Usage: [prefix]show_color <hexadecimal colour code>
```

```
Aliases: color, colour, sc
```

## - mystbin

Generate an Mystbin for yourself

Parameters Required: text

Usage: [prefix]mystbin <text>

Aliases: myst

## - getmystbin

Get your Mystbi using your id

Parameters Required: id

Usage: [prefix]getmystbin <mystbin\_id>

Aliases: getmyst

## - 8ball

Ask questions about your future

Parameters Required: question

Usage: [prefix]8ball <question>

## Developer

These set of commands are only locked to the developer

### - dev

These set of commands are only locked to the developer

Parameters Required: command

## - sharedservers

Parent: [dev](#)

Get a list of servers the bot shares with the user.

Parameters Required: user

Usage: [prefix]dev sharedservers <user>

## - changestat

Parent: [dev](#)

Change the bot status

## - stream

Parent: [dev](#) [changestat](#)

Streaming Activity

Parameters Required: activity

## - game

Parent: [dev](#) [changestat](#)

Game Activity

Parameters Required: activity

## - watching

Parent: [dev](#) [changestat](#)

Watching activity

Parameters Required: activity



## - listening

Parent: [dev changestat](#)

Listening Activity

```
Parameters Required: activity
```

## - post\_commands

Parent: [dev](#)

Posts commands to different botlist

```
Parameters Required: print_logs
```

```
Usage: [prefix]dev post_commands [print_logs]
```

```
Aliases: post_command
```

## - createinvite

Parent: [dev](#)

Create an invite to the specified server

```
Parameters Required: guild
```

```
Usage: [prefix]dev createinvite <server ID>
```

## - pretend

Parent: [dev](#)

Execute my commands pretending as others | usage: eg: )own as @Minato  
angel

```
Parameters Required: target, command_string
```

## - eval

Parent: [dev](#)

Evaluates python code

```
Parameters Required: body
```

## - post\_stats

Parent: [dev](#)

Posts stats to different botlist

```
Parameters Required: print_logs
```

```
Usage: [prefix]dev post_stats [print_logs]
```

## - sync

Parent: [dev](#)

Sync with GitHub and reload all the cogs

## Giveaway

Helps you to organise a simple giveaway.

## - giveaway

Allows you to to create giveaway by answering some simple questions!

```
Aliases: gcreate, gcr, giftcr
```

## - giftrrl

It picks out the giveaway winners

Parameters Required: giveaway\_id

Usage: [prefix]giftrrl <giveaway id> [channel]

Aliases: gifreroll, gftroll, grr, giftrroll, giveawayroll, giveaway\_roll, reroll

## - giftdel

Cancels the specified giveaway

Parameters Required: giveaway\_id

Usage: [prefix]giftdel <giveaway id>

Aliases: gifdel, gftdel, gdl

## Image Manipulation

Some fun Image Manipulation Commands

### - wni

Prove that you are not sus!

Parameters Required: member

Usage: [prefix]wni [member.mention | member.id]

### - wi

Prove anyone that they are sus!

Parameters Required: member

Usage: [prefix]wi [member.mention | member.id]

## - triggered

Make anyone triggered

Parameters Required: member

Usage: [prefix]triggered [member.mention | member.id]

## - message

Send a fake Discord message

Parameters Required: member, text

Usage: [prefix]message [discord.member.mention.to.send | member.id]  
<your.message>

## - captcha

Captcha v3 Image mockup

Parameters Required: member, text

Usage: [prefix]captcha <member.mention, captcha.text>

## - pixel

Pixallate your pfp

Parameters Required: member

Usage: [prefix]pixel [member.mention | member.id]

## - jail

Jail yourself or someone

Parameters Required: member

Usage: [prefix]jail [member.mention | member.id]

## - wanted

Get yourself or someone listed in Bingo Book

Parameters Required: member

Usage: [prefix]wanted [member.mention | member.id]

## - rainbow

Rainbow light effect

Parameters Required: member

Usage: [prefix]rainbow [member.mention | member.id]

## - gay

Seperate yourself/others and mark them/yourself as gay!

Parameters Required: member

Usage: [prefix]gay [member.mention | member.id]

## - trash

Puts trash into trashbin

Parameters Required: member

Usage: [prefix]trash [member.mention | member.id]

## - delete

Removes trash from bin

Parameters Required: member

Usage: [prefix]delete [member.mention | member.id]

Aliases: delete\_trash, dt

## - angel

Be an Angel

Parameters Required: member

Usage: [prefix]angel [member.mention | member.id]

## - satan

Be the Devil

Parameters Required: member

Usage: [prefix]satan [member.mention | member.id]

## - charcoal

Get your pfp beautiful charcoal paint

Parameters Required: member

Usage: [prefix]charcoal [member.mention | member.id]

Aliases: chp, chpaint, charcoal\_paint, charcoalp

## - hitler

Hail Hitler

Parameters Required: member

Usage: [prefix]hitler [member.mention | member.id]

## - wasted

GTA V wasted screen

Parameters Required: member

Usage: [prefix]wasted [member.mention | member.id]

## - bomb

Bomb someone

Parameters Required: member

Usage: [prefix]bomb [member.mention | member.id]

## - pat

Pat someone, UwU!

Parameters Required: member

Usage: [prefix]pat [member.mention | member.id]

## - spank

Spank someone

```
Parameters Required: member
```

```
Usage: [prefix]spank [member.mention | member.id]
```

## - slap

Slap someone

```
Parameters Required: member
```

```
Usage: [prefix]slap [member.mention | member.id]
```

## - hug

Hug someone

```
Parameters Required: member
```

```
Usage: [prefix]hug [member.mention | member.id]
```

## - poke

Poke someone

```
Parameters Required: member
```

```
Usage: [prefix]poke [member.mention | member.id]
```

## - high5

Do a highfive



Parameters Required: member

Usage: [prefix]high5 [member.mention | member.id]

## - party

Party with someone

Parameters Required: member

Usage: [prefix]party [member.mention | member.id]

## BackUp

Create a backup for your server

## - backup

Backup related commands

Parameters Required: command

## - apply

Parent: [backup](#)

Applies backup template to the server. This may take a lot of time.

Parameters Required: code

Usage: [prefix]backup apply <code>

## - template

Parent: [backup](#)

Create a backup of this guild, (it backups only those channels which is visible to the bot)

Aliases: templates

## - get

Parent: [backup](#)

Gets the json file which is stored as a backup

Parameters Required: code

Usage: [prefix]backup get <code>

## - channellogs

Parent: [backup](#)

Creat a backup of all channel data as json files This might take a long time

Parameters Required: channel, send

Usage: [prefix]backup channellogs [channel.mention | channel.id]

Aliases: channelbackup

## - delete

Parent: [backup](#)

Deletes the backup data if it is there in the database.

Parameters Required: args

Usage: [prefix]backup delete <args>

## - serverlogs

Parent: [backup](#)

Creates a backup of all server data as json files. This might take a long time.

```
Aliases: serverbackup
```

## - attachments

Parent: [backup](#)

Backups the attachment(s) of the specified channel or channel in which command was run.

```
Parameters Required: channel
```

```
Usage: [prefix]backup attachments [channel.mention]
```

# Moderation

Some simple moderation commands

## - setdelay

Sets Slowmode Of A Channel

```
Parameters Required: seconds
```

```
Usage: [prefix]setdelay <time in seconds>
```

## - kick

A command which kicks a given user

```
Parameters Required: member, reason
```

```
Usage: [prefix]kick <user> [reason]
```

## - ban

A command which bans a given user

```
Parameters Required: member, reason
```

```
Usage: [prefix]ban <user> [reason]
```

## - banlist

Shows list of users who have been banned! Or position of a specified user who was banned!

```
Parameters Required: member
```

```
Usage: [prefix]banlist [member.id ,member.mention or member.name.with.tag]
```

## - softban

Soft bans a member from the server.

```
Parameters Required: member, reason
```

## - unban

Unbans a member from the server.

```
Parameters Required: member, reason
```

## - ar

Adds a role to a given user

Parameters Required: member, role, reason

Usage: [prefix]ar <member.mention> <role>

## - multiban

Bans multiple members from the server.

Parameters Required: members, reason

## - massban

Mass bans multiple members from the server.

Parameters Required: args

## - warn

Warn a user

Parameters Required: member, reason

Usage: [prefix]warn <member.mention> [optional: reason]

## - warnlist

Get the no. of warns for a specified user

Parameters Required: member

Usage: [prefix]warnlist [member.mention]

## - newusers

Tells you the newest members of the server.

Parameters Required: count

Usage: [prefix]newusers [count]

Aliases: newmembers

## - cleanup

Cleans up the bot's messages from the channel.

Parameters Required: search

## - simeplepurge

A command which purges the channel it is called in

Parameters Required: amount

Usage: [prefix]simeplepurge [amount]

## - remove

Removes messages that meet a criteria.

Aliases: purge

## - custom

Parent: [remove](#)

A more advanced purge command.

Parameters Required: args

## - bot

Parent: [remove](#)

Removes a bot user's messages and messages with their optional prefix.

Parameters Required: prefix, search

Aliases: bots

## - user

Parent: [remove](#)

Removes all messages by the member.

Parameters Required: member, search

## - all

Parent: [remove](#)

Removes all messages.

Parameters Required: search

## - emoji

Parent: [remove](#)

Removes all messages containing custom emoji.

Parameters Required: search

Aliases: emojis

## - files

Parent: [remove](#)

Removes messages that have attachments in them.

Parameters Required: search

## - embeds

Parent: [remove](#)

Removes messages that have embeds in them.

Parameters Required: search

## - images

Parent: [remove](#)

Removes messages that have embeds or attachments.

Parameters Required: search

## - reactions

Parent: [remove](#)

Removes all reactions from messages that have them.

Parameters Required: search

## - contains

Parent: [remove](#)

Removes all messages containing a substring.

Parameters Required: substr



## - timeout

Timeout the member for a specified duration of time

Parameters Required: duration, member, reason

Aliases: mute

## - untimeout

Removes timeout from the member

Parameters Required: member, reason

Aliases: unmute

## - voicemute

Mutes the members from all the voice channels

Parameters Required: member, reason

Aliases: vc mute

## - voiceunmute

Unmutes the members all from the voice channels

Parameters Required: member, reason

Aliases: vcunmute

## - serverdeafen

Deafens the member from all the voice channels

Parameters Required: member, reason

Aliases: serverdeaf

## - serverundeafen

Un-deafen the member all from the server

Parameters Required: member, reason

Aliases: serverundeaf

## - suppress

Suppresses the members from all the stage channels

Parameters Required: member, reason

Aliases: stagesuppress, stagemute

## - unsuppress

Un-Suppresses the members from all the stage channels

Parameters Required: member, reason

Aliases: stageunsuppress, stageunmute

## - lock

### Locking Commands

## - threadchannel

Parent: [lock](#)

Locks the specified thread channel(s), both member and bot required  
Manage Thread perms to operate

Parameters Required: channels

Usage: [prefix]lock threadchannel [thread.channel]

Aliases: thread

## - textchannel

Parent: [lock](#)

Locks the specified text channel(s), both member and bot required  
Manage Channel perms to operate

Parameters Required: channels

Usage: [prefix]lock textchannel [text.channel]

Aliases: text

## - unlock

### Unlocking Commands

## - textchannel

Parent: [unlock](#)

Unlocks the specified text channel(s), both member and bot required  
Manage Channel perms to operate

Parameters Required: channels

Usage: [prefix]unlock textchannel [text.channel]

Aliases: text

## - threadchannel

Parent: [unlock](#)

Unlocks the thread channel in which the command was rrun, both member  
and bot required Manage Thread perms to operate

Usage: [prefix]unlock threadchannel [thread.channel]

Aliases: thread

## - jointhread

Joins the specified thread

Parameters Required: channel

Aliases: threadjoin

## AntiRaid

Antiraid system commands to use

### - raid

Controls raid mode on the server.

Aliases: raids, antiraid

## - off

Parent: [raid](#)

Disables raid mode on the server.

Aliases: disable, disabled

## - on

Parent: [raid](#)

Enables basic raid mode on the server.

Parameters Required: channel

Aliases: enable, enabled

## - strict

Parent: [raid](#)

Enables strict raid mode on the server.

Parameters Required: channel

## - mentionspam

Enables auto-banning accounts that spam mentions.

Parameters Required: count

## - ignore

Parent: [mentionspam](#)

Specifies what channels ignore mentionspam auto-bans.

Parameters Required: channels

Aliases: bypass

## - unignore

Parent: [mentionspam](#)

Specifies what channels to take off the ignore list.

Parameters Required: channels

Aliases: protect

## Server Setup

Do some necessary setup through an interactive mode.

## - setup

This commands setups some logging system for system for server with some nice features

## - starboard

Parent: [setup](#)

Setups the starboard in your server.

Parameters Required: channel, no\_of\_stars, self\_star, ignore\_nsfw

```
Usage: [prefix]setup starboard <channel> [no_of_stars] [self_star]
[ignore_nsfw]
```

## - add

Parent: [setup](#)

This command adds logging of the following things in the specified text channel

```
Parameters Required: add_type, channel
```

```
Usage: [prefix]setup add <add_type> <textchannel>
```

## - support

Parent: [setup](#)

Creates a **public support system** in an interactive manner.

```
Parameters Required: textchannel, support_required_role
```

```
Usage: [prefix]setup support <textchannel.mention> <support_required_role>
```

## - badlinks

Parent: [setup](#)

If enabled then it checks against any scam, phishing or adult links which is posted by members and take actions accordingly

```
Parameters Required: action, logging_channel, option
```

```
Usage: [prefix]setup badlinks <option> [action] [logging_channel]
```

## - raw\_data

It returns the raw data which is stored in the database in the form of json

## - deletedata

This command deletes the available data:

```
Parameters Required: type_data
```

```
Usage: [prefix]deletedata [type_data]
```

# Reaction Roles

Setup some reaction roles

## - rr

Reaction Roles related commands

```
Parameters Required: command
```

```
Aliases: reaction_roles
```

## - delete\_reaction\_roles

```
Parent: rr
```

It deletes the reaction roles

```
Parameters Required: reaction_roles_id
```

```
Usage: [prefix]rr delete_reaction_roles <reaction_roles_id aka message.id
```

```
Aliases: del_rr
```



- **new**

Parent: `rr`

Create a new reaction role using some interactive setup.

```
Aliases: create
```

## Badges

Create fun fake badges based on your discord profile

- **badges**

Creates a fun fake badge based on your discord profile

```
Parameters Required: badge
```

```
Aliases: badge
```

- **gbadges**

Creates a fun fake gif badge based on your discord profile

```
Parameters Required: badge
```

```
Aliases: gbadge
```

- **listbadges**

List the available badges that can be created

# Music

Listen to some soothing music!

## - join

Joins the voice channel

## - leave

Disconnects from a voice channel

## - play

Plays the requested music

```
Parameters Required: url
```

```
Usage: [prefix]play <music.url | music.name>
```

## - pause

Pauses the current music playing

## - resume

Resumes music

## - stop

Stops the Music Player

## - loop

Iterates the current playing song

- **queue**

Displays the songs queue

- **np**

Gives info about current playing song

- **skip**

Skips the current playing song

- **volume**

Changes the volume for the current song

```
Parameters Required: vol
```

```
Usage: [prefix]volume <value between 1-100>
```

```
Aliases: vol
```

- **remove\_song**

Song the specified song using its index value

```
Parameters Required: index
```

```
Usage: [prefix]remove_song <song.index.value>
```

## Jishaku

The frontend subclass that mixes in to form the final Jishaku cog.

## - pip

Parent: [jishaku](#)

Shortcut for 'jsh sh pip'. Invokes the system shell.

Parameters Required: argument

## - show

Parent: [jishaku](#)

Shows Jishaku in the help command.

## - repeat

Parent: [jishaku](#)

Runs a command multiple times in a row.

Parameters Required: times, command\_string

## - tasks

Parent: [jishaku](#)

Shows the currently running jishaku tasks.

## - override

Parent: [jishaku](#)

Run a command with a different user, channel, or thread, optionally bypassing checks and cooldowns.

Parameters Required: overrides, command\_string

Aliases: execute, exec, override!, execute!, exec!

## - cancel

Parent: [jishaku](#)

Cancels a task with the given index.

```
Parameters Required: index
```

## - load

Parent: [jishaku](#)

Loads or reloads the given extension names.

```
Parameters Required: extensions
```

```
Aliases: reload
```

## - debug

Parent: [jishaku](#)

Run a command timing execution and catching exceptions.

```
Parameters Required: command_string
```

```
Aliases: dbg
```

## - cat

Parent: [jishaku](#)

Read out a file, using syntax highlighting if detected.

```
Parameters Required: argument
```

## - source

Parent: [jishaku](#)

Displays the source code for a command.

Parameters Required: `command_name`

Aliases: `src`

## - invite

Parent: [jishaku](#)

Retrieve the invite URL for this bot.

Parameters Required: `perms`

## - shutdown

Parent: [jishaku](#)

Logs this bot out.

Aliases: `logout`

## - rtt

Parent: [jishaku](#)

Calculates Round-Trip Time to the API.

Aliases: `ping`

## - curl

Parent: [jishaku](#)

Download and display a text file from the internet.

Parameters Required: url

## - retain

Parent: [jishaku](#)

Turn variable retention for REPL on or off.

Parameters Required: toggle

## - permtrace

Parent: [jishaku](#)

Calculates the source of granted or rejected permissions.

Parameters Required: channel, targets

## - py

Parent: [jishaku](#)

Direct evaluation of Python code.

Parameters Required: argument

Aliases: python

## - ast

Parent: [jishaku](#)

Disassemble Python code into AST.

Parameters Required: argument

## - `py_inspect`

Parent: [jishaku](#)

Evaluation of Python code with inspect information.

Parameters Required: argument

Aliases: `pyi`, `python_inspect`, `pythoninspect`

## - `dis`

Parent: [jishaku](#)

Disassemble Python code into bytecode.

Parameters Required: argument

Aliases: `disassemble`

## - `voice`

Parent: [jishaku](#)

Voice-related commands.

Aliases: `vc`

## - `resume`

Parent: [jishaku voice](#)

Resumes a running audio source, if there is one.

## - `disconnect`

Parent: [jishaku voice](#)



Disconnects from the voice channel in this guild, if there is one.

Aliases: dc

## - volume

Parent: [jishaku voice](#)

Adjusts the volume of an audio source if it is supported.

Parameters Required: percentage

## - play

Parent: [jishaku voice](#)

Plays audio direct from a URI.

Parameters Required: uri

Aliases: play\_local

## - join

Parent: [jishaku voice](#)

Joins a voice channel, or moves to it if already connected.

Parameters Required: destination

Aliases: connect

## - stop

Parent: [jishaku voice](#)

Stops running an audio source, if there is one.

## - youtube\_dl

Parent: [jishaku voice](#)

Plays audio from youtube\_dl-compatible sources.

Parameters Required: url

Aliases: youtubedl, ytdl, yt

## - pause

Parent: [jishaku voice](#)

Pauses a running audio source, if there is one.

## - git

Parent: [jishaku](#)

Shortcut for 'jsh sh git'. Invokes the system shell.

Parameters Required: argument

## - hide

Parent: [jishaku](#)

Hides Jishaku from the help command.

## - shell

Parent: [jishaku](#)

Executes statements in the system shell.

Parameters Required: argument

Aliases: bash, sh, powershell, ps1, ps, cmd, terminal

## - unload

Parent: [jishaku](#)

Unloads the given extension names.

Parameters Required: extensions

Last update: March 13, 2022

Created: March 5, 2022